MARYLAND NUTRIENT MANAGEMENT MANUAL

Incorporated by reference into COMAR 15.20.07

Supplement No. 8

(November 2014)

The instructions below should be followed carefully. Remove the obsolete pages listed under the column "Remove Pages." Insert the new pages listed under the column "Insert Pages."

ALL PAGES ARE INCLUSIVE

<u>Nutrient Mgt. Manual</u>	Remove <u>Pages</u>	Insert <u>Pages</u>
Table of Contents	i - ii	i - ii
Phosphorus Site Index for Maryland (University of Maryland Cooperative Extension, September 2000)	II-C1 — II-C8 II-C Attachment 1	II-C1-1 — II-C1-8 II-C2-Attachment 1
University of Maryland Phosphorus Management Tool: Technical Users Guide (University of Maryland Extension, 2013)		II-C2-1 — II-C2-16

TABLE OF CONTENTS

SECTION I. NUTRIENT RECOMMENDATIONS (BLUE TABS)

A. Introduction

B. Nutrient Recommendations by Crop

- 1. Agronomic Crop Nutrient Recommendations Based on Soil Tests and Yield Goals (University of Maryland Cooperative Extension, 2012)
- 2. Plant Nutrient Recommendations Based on Soil Tests for Vegetable Crop Production (University of Maryland Cooperative Extension, 2009)
- 3. Plant Nutrient Recommendations Based on Soil Tests for Sod Production (University of Maryland Cooperative Extension, 1999)
- 4. Nutrient Recommendations for Commercial Christmas Tree Production (University of Maryland Cooperative Extension, 2001)
- 5. Nutrient Management Recommendations for Commercial Cut Flower Production (University of Maryland Cooperative Extension, 2009)
- 6. Nutrient Management for Tree Fruits and Small Fruits (University of Maryland Cooperative Extension, 2003)
- 7. Nutrient Recommendations for Commercial Loblolly Pine Plantations in Maryland (University of Maryland cooperative Extension, 2006)
- C. Estimated Mineralization Rates, Nitrogen Credits for Legumes, and Ammonia Conservation Factors for Organic Nitrogen (University of Maryland Cooperative Extension, 2009)
- **D. Nutrient Application Requirements** (Maryland Department of Agriculture, 2012)
- E. Nutrient Recommendations for Non-Agricultural Land
 - Plant Nutrient Recommendations Based on Soil Tests for Turf Maintenance (University of Maryland Cooperative Extension, 1999)
 - 2. Nutrient Management Guidelines for Commercial Turfgrass Seeding (University of Maryland Cooperative Extension, 2005)

i

SECTION II. ENVIRONMENTAL RISK ASSESSMENT TOOLS (YELLOW TABS)

- A. Introduction
- **B.** Converting Among Soil Test Analyses Frequently Used In Maryland (University of Maryland Cooperative Extension, 2006)
- C. Phosphorus Risk Assessment Tools

1. Phosphorus Site Index for Maryland (University of Maryland Cooperative Extension, September, 2000)

- **2. University of Maryland Phosphorus Management Tool: Technical Users Guide** (University of Maryland Cooperative Extension, 2013)
- **D. Environmental Risk Assessment for Out-Of-Ground Production** (Maryland Department of Agriculture, 2000)
- **E. Best Management Practices for Container-Grown Plants** (Southern Nurserymen's Association, 1997)

SECTION III. ANIMAL MANURE AND WASTE MANAGEMENT (GRAY TABS)

- A. Introduction
- **B.** Animal Unit Equivalencies (Maryland Department of Agriculture, 2000)
- C. Manure Management (Maryland Department of Agriculture, 1999)
- D. Manure Management Evaluation Form (Maryland Department of Agriculture, 1999)
- **E.** Agricultural Waste Characteristics (USDA Natural Resources Conservation Service, Agricultural Waste Management Field Handbook, 2008)
- F. Guidelines for Application of Soil Conditioners, Soil Amendments, Waste Materials or Effluent on Agricultural Land (Summary of Existing Guidlines) (Maryland Department of Agriculture, 2012)

NUTRIENT MANAGEMENT LAW & REGULATIONS (GREEN TABS)

Table of Contents

Maryland Nutrient Management Laws §§8-801 et seq.

Nutrient Management Regulations COMAR 15.20.04, 15.20.05, 15.20.06, 15.20.07, 15.20.08

Maryland Commercial Fertilizer Laws §§6-201 et seq.

Definitions of Identity for Commercial Fertilizer COMAR 15.18.01

Sewage Sludge Management COMAR 26.04.06

Animal Feeding Operations (CAFO/MAFO) Updated Guidelines

PHOSPHOROUS SITE INDEX FOR MARYLAND

Source: University of Maryland Cooperative Extension, September, 2000 Regulatory Citation: COMAR 15.20.08.05E

The nutrient management regulations identify the Phosphorus Site Index (P-index) as the primary tool to be used for evaluating the potential risk for phosphorus movement from agricultural land to state waters. It is used when soil fertility index values are greater than 150 to determine the limiting nutrient and identify required management as delineated by COMAR 15.20.08.04E(3).

Definition

The Phosphorus Site Index is a tool that can be used to evaluate the potential P soil losses as they relate to certain site characteristics and management practices. This tool provides nutrient management planners and farmers with a method to evaluate their fields and to make management decisions based on the values obtained from the P-index.

How to Use the P-Index

The P-index evaluates potential P losses in two steps. Part A evaluates potential phosphorus loss due to site and transport characteristics, and Part B evaluates potential phosphorus loss due to management practices.

Part A: Phosphorus loss potential due to site and transport characteristics

-Soil Erosion (estimate tons soil loss /acre/year, using the NRCS Field Office Technical Guide)

-Soil test P Fertility Index Value or FIV (using the soil test results)

-Soil Runoff Class

-Subsurface Drainage

-Leaching Potential (using the NRCS Field Office Technical Guide)

-Distance from Edge of Field to Surface water or Drainage (using the map or site measurement in feet)

-Priority of Receiving Water

Part B: Phosphorus Loss Potential Due to Management Practices

-Soil Test P- fertility index value conversion (see "Converting among Soil Test Analyses Frequently Used in Maryland")

-P Fertilizer Application Rate (lbs P₂O₅/ acre)

-P Fertilizer Application Method

-Organic P Application Rate (lbs P₂O₅/ acre)

-Organic P Source Application Method

Characteristics	Phosphorus L	Phosphorus Loss Rating				Value
Soil Erosion (tons/acre)	2 X tons soil los	2 X tons soil loss/acre/year				
	Negligible or Very Low	Low	Medium	High	Very High	
Soil Runoff Class	0	2	4	6	8	
Subsurface	Very Low	Low	Medium	High	Very High	
Drainage	0	2	4	6	8	
Leaching Potential	Low		Medium	High		
		0	2	4	4	
Distance From Edge of Field to Surface Water (feet)	> 100 feet 0	< 100 feet AND >50 feet vegetated buffer OR <100 feet AND > 25 feet vegetated buffer AND > 25 feet additional no P application zone 2	< 100 feet AND > 25 feet vegetated buffer AND < 25 ft additional no P application zone 4	< 100 feet AND < 25 feet vegetative buffer AND > 25 feet additional no P application zone 6	< 100 feet AND < 25 feet vegetative buffer AND < 25 ft additional no P application zone 8	
	Category 2	Category 3	Category 3,	Category 1	Category 1,	
Priority of Receiving	0	1	Selected	3	Priority	
water	U	1	2	3	4	

Part A: Phosphorus loss potential due to site and transport characteristics

Sum of Site and Transport Characteristics:_____

Scaling Factor: x 0.02

Total Site and Transport Value: _____

Part B: Phosphorus loss potential due to management practice and source characteristics

Characteristics	Phosphorus Loss Rating V				Value	
Soil Test P Fertility Index Value		0.2 X FIV				
P Fertilizer Application Rate (lbs P ₂ O ₅)		0.6 X (lbs $P_2O_5/acre$)				
P Fertilizer Application Method	None applied 0	Injected/ Banded below surface at least 2" 15	Incorporated within 5 days of application 30	Surface applied March through November OR Incorporated more than 5 days after application 45	Surface applied December through February 60	
Organic P Application Rate (lbs P ₂ O ₅)	PAC X (lbs P_2O_5 / acre)					
Organic P Application Method	None applied 0	Injected/bande d below surface at least 2" 15	Incorporated within 5 days of application 30	Surface applied March through November OR Incorporated more than 5 days after application 45	Surface applied December through February 60	

Total Management and Source Value:_____

PHOSPHORUS INDEX WORKSHEET

To solve for P loss rating - add all numbers on Part A and all numbers on Part B. Write these numbers on the worksheet. Multiply Part A x Part B. This is your final P loss rating.

Part A: Value:_____

Part B: Value:_____

Multiply A x B = _____ P Loss Rating

P Loss Rating	Generalized Interpretation of P Loss Rating
0-50	LOW potential for P movement from this site given current management practices and site characteristics. There is a low probability of an adverse impact to surface waters from P losses from this site. Nitrogen-based nutrient management recommendations are approved for this site. Soil P levels and P loss potential may increase in the future due to N-based nutrient management.
51-75	MEDIUM potential for P movement from this site given current management practices and site characteristics. A nitrogen-based plan may be implemented no more than one year out of three. Phosphorus rates during the other two years shall be limited to the expected amount removed from the field by the crop or plant harvest, or the amount indicated by soil testing in accordance with recommendations described in the <u>Maryland Nutrient Management Manual</u> , whichever is greater.
76-100	HIGH potential for P movement from this site given current management practices and site characteristics. Phosphorus rates shall be limited to <i>the expected amount removed from the field by the crop or plant harvest</i> , or the amount indicated by soil testing in accordance with recommendations described in the <u>Maryland Nutrient Management Manual</u> , <i>whichever is greater</i> . All practical management practices for reducing P losses by surface runoff, subsurface flow, or erosion shall be implemented.
>100	VERY HIGH potential for P movement from this site given current management practices and site characteristics. No phosphorus should be applied to this site. All practical management practices for reducing P losses by surface runoff, subsurface flow, or erosion shall be implemented.

TABLE 1: THE SURFACE RUNOFF CLASS

Table 1–The Surface Runoff Class site characteristic determined from the relationship of the soil permeability class and field slope. Adapted from the soil survey manual (1993) Table 3-10.

Soil Permeability Class*					
Slope (%)	Very Rapid	Moderately Rapid and Rapid	Moderately Slow and Moderate	Slow	Very Slow
Concave**	Ν	N	Ν	Ν	Ν
<1	Ν	N	Ν	L	М
1-5	Ν	VL	L	М	Н
5-10	VL	L	М	Н	VH
10-20	VL	L	М	Н	VH
>20	L	М	Н	VH	VH

N = Negligible

M = Medium

VL = Very low

L = Low

H = High

VH = Very high

* Permeability class of the least permeable layer within the upper 39 inches (one meter) of the soil profile. Permeability classes for specific soils can be obtained from a published soil survey or from local USDA-NRCS field offices.

Soil permeability Classes in inches per hour (in/hr): very slow (<0.06 in/hr) slow (0.06 - 0.20 in/hr) moderately slow (0.20 - 0.60 in/hr) moderate (0.60 - 2.00 in/hr) moderately rapid (2.00 - 6.00 in/hr)

** Area from which no or very little water escapes by overland flow.

TABLE 2: SUBSURFACE DRAINAGE POTENTIAL

Depth to	Soil Drainage Class						
Seasonal High Water Table (feet)	very poorly drained	poorly drained	somewhat poorly drained	moderately well drained	well- drained soils	somewhat excessively drained	excessively drained
0 - 1	Н	VH	VH	VH	VH	VH	
1 - 3	М	М	М	М	Н	Н	Н
3 - 6	L	L	L	L	М	М	М
> 6		VL	VL	L	L	L	L
Artificial Subsurface Drainage (any depth)	Н	Н	Н	Н	Н	Н	Н

VL = Very low L = Low M = Medium H = HighVH = Very high

II-C1-5

TABLE 3: PRIORITY OF RECEIVING WATERS-MARYLAND STATE WATERSHEDS

Very Low (0)

02130101	Atlantic Ocean
02130607	Christina River
Low (1)	
LOW (1)	Company on Caral
02050501	Conewago Creek
02130402	Little Choptank
02130501	Eastern Bay
02130504	Kent Narrows
02130605	Little Elk Creek
02131106	Middle Patuxent River
02130104	Sinepuxent Bay
02130403	Lower Choptank
02130502	Miles River
02130505	Lower Chester River
02130705	Aberdeen Proving Ground
02140301	Potomac River FR County
Medium (2)	
02120203	Octoraro Creek
02130106	Chincoteague Bay
02130204	Diving Creek
02130206	Tangier Sound
02130302	Monie Bay
02130306	Marshyhope Creek
02130401	Honga River
02130508	Southeast Creek
02130601	Lower Elk River
02130606	Big Elk Creek
02130702	Lower Winters Run
02130801	Gunpowder River
02130804	Little Gunpowder Falls
02130906	Patansco River LN
02131001	Magothy River
02131005	West Chesapeake Bay
02131108	Brighton Dam
02140105	St Clements Bay
02140108	Zekiah Swamp
02140202	Potomac River MO County
02140501	Potomac River WA County
02140505	Little Conococheague
02140508	Potomac River AL County
02140508	Wills Creek
02120205	Broad Creek
02120205	Pocomoke Sound
02130205	Nassawango Creek
02130203	Rig Annemessay Diver
02130207	Wisemise Creek
02130303	wicomico Ureek
02130307	Fisning Bay
02130404	Upper Choptank

II-C1-6

TABLE 3: PRIORITY OF RECEIVING WATERS-MARYLAND STATE WATERSHEDS

Medium (2) ... continued

02130510	Upper Chester River
02130602	Bohemia River
02130609	Furnace Bay
02130703	Atkisson Reservoir
02130802	Lower Gunpowder Falls
02130805	Loch Raven Reservoir
02130908	S. Branch Patapsco
02131004	West River
02131107	Rocky Gorge Dam
02140101	Potomac River Lower Tidal
02140106	Wicomico River
02140201	Potomac River Upper Tidal
02140304	Double Pipe Creek
02140503	Marsh Run
02140506	Licking Creek
02140509	Little Tonoloway Creek
05020202	Little Youghiogheny River
High (4)	
02130102	Assawoman Bay
02130105	Newport Bay
02130208	Manokin River
02130304	Wicomico River Headwaters
02130405	Tuckahoe River
02130507	Corsica River
02130511	Kent Island Bay
02130610	Sassafras River
02130701	Bush River
02130706	Swan Creek
02130807	Middle River-Browns Creek
02130902	Bodkin Creek
02130904	Jones Falls
02131003	South River
02131103	Western Branch
02131105	Little Patuxent River
02140203	Piscataway Creek
02140205	Anacostia River
02140207	Cabin John Creek
02140305	Catoctin Creek
05020203	Deep Creek Lake
02130103	Isle of Wight Bay
02130203	Upper Pocomoke River
02130301	Lower Wicomico River
02130308	Transquaking River
02130506	Langford Creek
02130509	Middle Chester River
02130604	Back Creek
02130611	Stillpond-Fairlee
	~ mpond i united

TABLE 3: PRIORITY OF RECEIVING WATERS-MARYLAND STATE WATERSHEDS

High (4) ... continued

02130704	Bynum Run
02130803	Bird River
02130901	Back River
02130903	Baltimore Harbor
02131002	Severn River
02131102	Patuxent River Middle tidal
02131104	Patuxent River upper
02140104	Breton Bay
02140204	Oxon Creek
02140206	Rock Creek
02140208	Seneca Creek
02140504	Conococheague Creek

Very High (8)

Lower Susquehana River
Conowingo Dam Susq.Run
Nanticoke River
Upper Elk River
Prettyboy Reservoir
Liberty Reservoir
Potomac River Middle tidal
Gilbert Swamp
Nanjemoy Creek
Lower Monocacy River
Antietam Creek
Sideling Hill Creek
Town Creek
Evitts Creek
Potomac River Upper N.Br.
Youghiogheny River
Deer Creek
Lower Pocomoke River
Wye River
Northeast River
Gwynns Falls
Patuxent River Lower tidal
St.Mary's River
Port Tobacco River
Mattawoman Creek
Upper Monocacy River
Tonoloway Creek
Fifteen Mile Creek
Potomac River Lower N.Br.
Georges Creek
Savage River
Casselman River

ATTACHEMENT 1: REVISED UNISERVAL SOIL LOSS EQATION (RUSLE)

Source: USDA Natural Resources Conservation Service, 1995

The Revised Universal Soil Loss Equation (RUSLE) is a soil erosion prediction tool that identifies the factors that are a part of the interaction of rain and soil. While similar to the Universal Soil Loss Equation (USLE), RUSLE adds more specifics to the factors of the equation. These factors are quantified as the equation:

$\mathbf{A} = \mathbf{R} \times \mathbf{K} \times \mathbf{LS} \times \mathbf{C} \times \mathbf{P}$

A, the predicted soil loss, is a product of:

R	=	Rainfall erosivity	Rain-related factor
Κ	=	Soil erodibility	
L	=	Slope length	Soil-related factors
S	=	Slope gradient or steepness)
С	=	Cover and management	
Р	=	Erosion control practices	} Land management factors

Rainfall erosivity factor R represents the driving force for sheet or rill erosion. It takes into consideration total rainfall, intensity and seasonal distribution of the rain. R is generally he same in the two equations; however, RUSLE computes a correction to R to reflect, for flat land, he effect of raindrop impact on water ponded on the surface.

Soil erodibility factor K indicates a soil's inherent susceptibility to erosion. Two important soil characteristics influencing erodibility are the infiltration capacity of the soil and the soil's structural stability. RUSLE accounts for season change in the soil such as freezing, thawing, soil moisture, and soil consolidation.

Topographic factors LS reflect the influence of length and steepness of slope on soil erosion. RUSLE refines USLE by assigning new equations based on the ration of rill to interrill erosion and accommodates complex slopes.

Cover and management factor C is the ratio of soil loss under the conditions in question to that which would occur under continuously bare soil. C uses subfactors: prior land use, canopy cover, surface cover and roughness, and soil moisture. RUSLE divides each year in the rotation into 15-day intervals, calculating the soil loss ratio for each time period. It also recalculates a new soil loss ratio every time a tillage operation changes one of the subfactors.

Support practice factor P is the ration of soil loss with a given support practice (generally, a best management practice) to the corresponding loss if there were no support practices. P factor values are based on hydrologic soil groups, slope row grade, ridge height, and the 10-year single storm erosion index value. RUSLE computes the effect of strip cropping based on the transport capacity of flow in dense strips relative to the amount of sediment reaching the strip. The P factor for conservation planning considers the amount and locations of deposition.

UNIVERSITY OF MARYLAND E X T E N S I O N

Solutions in your community

University of Maryland Phosphorus Management Tool: Technical Users Guide

The Phosphorus Index Concept

In 1990, a national cooperative workgroup of scientists from numerous universities and the United States Department of Agriculture (USDA) was organized to develop a procedure that could identify soils, farm management practices, and specific locations within a farm where phosphorus (P) losses in field drainage water may pose the potential for negative environmental impacts on nearby surface waters. The goals of this national work group were:

- To develop an easily used field rating system that rates farm fields according to the potential for P loss to surface water (the Phosphorus Index).
- To relate the P Index to the sensitivity of receiving surface waters to eutrophication and degradation resulting from nonpoint source P enrichment.
- To facilitate adaptation and modification of the P Index to regional and site-specific conditions.
- To develop agricultural management practices that will minimize the buildup of soil P to excessive levels and the transport of P from soils to sensitive water bodies.

The Objective of the University of Maryland Phosphorus Management Tool

Our objective was to develop a phosphorus site index (PSI) that uses readily available information to evaluate the relative risk of P transport from agricultural fields, including vegetable and row crop production and pasture based systems where P may be applied either as inorganic or organic fertilizer. Furthermore, the PSI should be applicable within all physiographic provinces present in Maryland. Phosphorus transport is controlled by site characteristics (e.g. hydrology and slope), climate, and P sources (e.g. manure, inorganic fertilizer, and soil P). The revised PSI, or the University of Maryland – Phosphorus Management Tool (UM-PMT), seeks to include new science relative to site and source factors and highlight management decisions so that the learning opportunities associated with performing a P index are more pronounced. The overall objective is to identify critical areas where there is a high P loss potential due to both a high transport potential and a large source of P, and also to encourage the use of management practices in those critical source areas that protect water quality.

Development of the University of Maryland – Phosphorus Management Tool

In 1994, we began the development of a P Index tool specifically tailored to Maryland's soils, agricultural management practices, climate, topography, hydrology, and surface water characteristics. The Maryland PSI

was originally based on the generalized national model published in 1993 by the USDA's Natural Resources Conservation Service, but it has undergone many substantive changes and modifications during its development to more accurately reflect Maryland conditions.

An Overview of How the University of Maryland – Phosphorus Management Tool Works

Equation 1 presents the generalized equation for the new University of Maryland Phosphorus Management Tool (UM-PMT), which replaces the 2005 Maryland PSI. The UM-PMT calculates the risk of P transport through surface runoff (RUNOFF), subsurface discharge (SUBSURFACE), and particulate bound P (PARTICULATE). In Eq. 1, DBF represents the combined distance and buffer factors; DPR_r and DPR_{sub} are the dissolved P source risk factors for runoff and subsurface losses, respectively; SD is the subsurface drainage transport factor; SR is the surface runoff transport factor; and SED is the sediment transport factor derived from RUSLE or RUSLE2. The construction of each of these factors is discussed in detail below. In general, the new arithmetic construction captures the intent of the original P index. It still identifies the areas where high transport potential and high source are present, but it does so separately for each of the three major P transport pathways.

Equation 1. General equation for the University of Maryland – Phosphorus Management Tool.

Interpretation of the Final Scores

The final P loss ratings are divided into three interpretative categories: low, medium, and high. Fields that score less than or equal to 50 are considered to present a low potential for P movement from the site. However, since according to current Maryland state regulations, all fields evaluated by the UM-PMT have soil test P greater than 150 FIV, which is considered excessive by agronomic standards, some risk exists relative to potential build-up of soil P concentrations due to application of P in excess of crop needs. Therefore, it is recommended that total P applied in a three year period not exceed the anticipated three year crop removal rate for P based on realistic yield goals and published crop removal rates. The intent is to prevent further buildup of soil P and therefore increase risk.

Fields that score from 51 – 100 present a medium potential for P movement from the site. They likely have intermediate soil P concentrations and soil P saturation, combined with moderate transport potential in one or more transport categories. Therefore, the recommendation is to limit P application within a single year to a one year crop removal rate of P based on realistic yield goals and published crop removal rates. The intent is to prevent further buildup of soil P and also protect against incidental transfer of organic or inorganic nutrients associated with higher application rates.

Finally, fields scoring greater than 100 are considered to have a high potential for P movement. They likely have high soil P concentrations and soil P saturation combined with high transport potential. No P should be applied to these sites and active remediation techniques (e.g. crop drawdown of soil P, dissolved P filters, or drainage management) should be implemented in order to reduce the potential for P movement from the site.

Gathering All Appropriate Information

The following is a list of information needed to determine the UM-PMT, as well as the source from which to obtain the information.

Information Source #1: Farm Operator

- Soil-test P converted to Maryland Fertility Index Value (FIV) units from soil-test report
- Degree of P saturation (DPS_{M3}) predicted by Mehlich 3 from soil test report
- Amount, analysis and type of P fertilizer applied
- Application method and timing of P fertilizer application
- Amount and type of manure, compost or biosolids applied
- Application method and timing for manure, compost, or biosolids application
- Manure, compost, or biosolids analysis
- Type and width of vegetated field buffers
- Crop rotation sequence
- Tillage rotation sequence
- Conservation practices such as strip or contour cropping, buffer strips, etc.

• Artificial drainage areas (drainage ditches, tile drains, or mole drains)

Information Source #2: Web Soil Survey

- Predominant soil mapping unit in the field
- Soil permeability class
- Soil drainage class
- Hydrology soil group

Information Source #3: Field Visit

• Distance from edge of the field to the nearest down gradient surface water (feet)

• Slope of field (length and steepness)

Information Source #4: RUSLE or RUSLE2 Calculation Capability

• RUSLE "P" practices: ridge height, furrow grade, cover management condition, number of crop strips across RUSLE slope, width of crop and/or buffer strips

Supplies Necessary for Data Collection

The following is a list of supplies and equipment that are necessary for collecting P Site Index data:

- UM-PMT Technical Users Guide
- Maryland Nutrient Management Training Manual
- Web Soil Survey
- Clinometer or similar slope measuring device
- Measuring wheel or measuring tape

Calculating the UM-PMT

On the following pages are detailed instructions on how to calculate the three components of the UM-PMT and determine the final score.

II-C2-3

Calculating the University of Maryland Phosphorus Management Tool

Combined Distance and Buffer Factor

Equation 2. Combined distance buffer factor calculation.

$$DBF = DF * BF$$

Equation 2 presents the calculation for the combined Distance-Buffer Factor (DBF). The DBF accounts for management and land cover of the intervening area between the managed field and surface water receiving runoff. The user should select the Distance Factor (DF) from Table 1 based on the distance from the edge of the field to the nearest body of surface water that receives surface discharge from the field. The user should also select the appropriate Buffer Factor (BF) from Table 2. The Distance-Buffer Factor (DBF) is applied to the transport components for dissolved P and particulate P in runoff, presented as RUNOFF and PARTICULATE in Eq. 1, respectively. The DBF will NOT be applied to subsurface transport (SUBSURFACE, Eq. 1), since subsurface transport of P is not controlled to the same extent by distance from water or intervening land cover as surface transported P.

Table 1. Distance from edge of field to surface water[†] and resulting distance factor.

Distance from Surface Water	Distance Factor (DF)
>500 feet	0.2
350 to 500 feet	0.4
200 to 349 feet	0.6
100 to 199 feet	0.8
<100 feet	1.0

⁺Surface water includes any permanent, continuous, physical conduit for transporting surface water, including permanent streams and ditches even if they only flow intermittently during the course of the year.

Table 2. Types of buffers⁺ and resulting buffer factors that will modify the Distance Risk Factor to yield the combined Distance Buffer Factor.

Type of Buffer	Buffer Factor (BF)	
>50 feet Permanent Vegetated Buffer Meeting USDA-NRCS Standards	0.8	
>35 feet Permanent Vegetated Buffer	0.9	
<35 feet Vegetated Buffer or No Buffer	1.0	
[†] Permanent vegetated buffers do not receive any phosphorus applications.		

Source Risk Factors for Dissolved Phosphorus

The RUNOFF and SUBSURFACE components from Eq. 1 describe the transport of dissolved P, which can originate from desorbable soil P or soluble P in organic or inorganic amendments. The UM-PMT includes separate dissolved P risk factors for the surface runoff (DPR_r) and subsurface discharge components (DPR_{sub}). The generalized form for both is presented in Equation 3.

Equation 3. Subsurface and runoff dissolved P source risk factor calculation.

$$DPR = WSP_{app} + (2 * DPS_{M3})$$

The subsurface and runoff dissolved P source risk factor (DPR_{sub} & DPR_r represent the combination of soluble P applied, the method it is applied by, and the amount of soluble P already in the soil (Eq. 5). DPR_r and DPR_{sub} are calculated by summing the water soluble P application factor (WSP_{app}) and two times the degree of P saturation (DPS_{M3}) predicted by Mehlich 3 extractable P, Fe, and Al as per Sims et al. (2002). The same value for DPS_{M3} should be used for both DPR_r and DPR_{sub}; however, WSP_{app} will be different for DPR_r and DPR_{sub}. Equation 4 describes the water soluble P application factor (WSP_{app}) that is used to represent the risk posed by the total amount of soluble P applied and the method used to apply it.

Equation 4. Water soluble phosphorus application factor for subsurface and runoff dissolved P source risk factor.

$$\sum_{0}^{n} WSP_{app-sub} = \sum_{0}^{n} PSC *TP * AM_{sub}$$
$$\sum_{0}^{n} WSP_{app-r} = \sum_{0}^{n} PSC *TP * AM_{r}$$

The WSP_{app} is calculated by multiplying the P source coefficient (PSC) for each source by the planned total P application rate (TP) for that source and the application method factor (AM_{sub} or AM_r). The AM represents the risk posed by the application method and is taken from Table 3 for DPR_{sub} and Table 4 for DPR_r. The WSP_{app} should be calculated separately for each planned P application (e.g. starter fertilizer, biosolids, manure) and then the separate WSP_{app} factors should be summed. This will account for the cumulative risk posed by the application of P at multiple times to both surface and subsurface discharge. The PSC's account for the varying solubility of different sources of P and are provided in Table 5 or the PSC can be determined individually by analyzing the amendment for WEP₁₀₀ and using Eq. 5. If laboratory data is not available and an amendment is not listed in Table 5 then a standard PSC of 0.6 should be used. If calculating the actual PSC of an amendment using Eq. 5, the method described by Elliott et al. (2006) should be used, where WEP₁₀₀ is the water-extractable P in the amendment (g kg⁻¹) determined in the laboratory using the method of Kleinman et al. (2007).

Equation 5. Phosphorus source coefficient calculation using water-extractable phosphorus concentration (Elliott et al., 2006).

$$PSC = 0.117 * WEP_{100}$$

Application Method	Value
None Applied	0
Incorporated within 5 days with soil mixing (precludes straight aerator) March - Nov.	0.32
Incorporated within 5 days with soil mixing (precludes straight aerator) Dec Feb.	0.4
Surface applied and subsurface placement without soil mixing (includes banded fertilizer and injection without soil mixing) March - Nov.	0.64
Surface applied and subsurface placement without soil mixing (includes banded fertilizer) Dec Feb.	0.8

Table 3. Phosphorus application method factor for subsurface transport component (AM_{sub}).

Table 4. Phosphorus application method factor for surface transport component (AM_r).

Application Method	Value
None Applied	0
Subsurface placement or immediate full incorporation (>90% residue)	0.2
Incorporated within 5 days of application (≥50% residue)	0.4
Surface applied March - Nov. OR incorporated after 5 days OR <50% residue	0.6
Surface applied or incorporated after 5 days Dec Feb.	0.8

Table 5. Standard phosphorus source coefficients for organic and inorganic amendments.

Organic P Source	PSC
Default	0.6
Inorganic P fertilizer	0.6
Swine manure	0.6
Other manures (beef, dairy, poultry, horse, etc.)	0.5
BPR & BNR biosolids	0.5
Alum-treated manures	0.3
Biosolids (all except BPR & BNR biosolids)	0.2

Subsurface Dissolved Phosphorus Discharge Component

The subsurface discharge component of the UM-PMT is presented as SUBSURFACE in Eq. 1 and represents the risk of dissolved P being transported to surface water through subsurface pathways. The calculation for this component is given in Eq. 6 below. If artificial drainage (e.g. ditches, tile drains) is present, then SUBSURFACE should be calculated. If artificial drainage is not present, then SUBSURFACE has a value of zero. SUBSURFACE is calculated by multiplying the subsurface drainage transport factor (SD) by the DPRsub (described above). The SD should be taken from Table 6, which is calculated by a matrix of the risk factors associated with soil drainage class for the dominant soil type in the field and then determine the SD where the two intersect using Table 6.

Equation 6. Subsurface dissolved phosphorus discharge calculation.

Hydrologic Soil Group А В С D Risk Soil Drainage Class Factor 1 1.2 1.2 1 Very Poorly Drained 8 8.0 6.7 6.7 8.0 **Poorly Drained** 7 7.0 5.8 5.8 7.0 Somewhat Poorly Drained 6 6.0 5.0 5.0 6.0 5 5.0 5.0 Moderately Well Drained 4.2 4.2 Well Drained 6 6.0 5.0 5.0 6.0 Somewhat Excessively Drained 7 7.0 5.8 5.8 7.0 6.7 6.7 8.0 **Excessively Drained** 8 8.0

$SUBSURFACE = SD * DPR_{sub}$

Table 6. The subsurface drainage transport factor (SD) is calculated as a function of hydrologic soil group and soil drainage class of the dominant soil type in the field.

Runoff Dissolved Phosphorus Component

The risk of dissolved P transport in overland flow is represented by the RUNOFF component of Eq. 1 and presented below in Eq. 7. It includes the DBF and the DPR_r, both described previously (Eqs. 2 and 3, respectively), which are then multiplied by the surface runoff transport risk factor (SR). The appropriate value for SR is where soil permeability class and slope of the dominate runoff generating area of the field intersect on Table 7.

Equation 7. Calculation for the runoff dissolved phosphorus component.

$RUNOFF = DBF * SR * DPR_r$

Table 7. Surface runoff transport risk factor (SR) based on field slope and soil permeability class.

	Soil Permeability Class [†] (inches/hour)				
		Moderately Rapid	Moderately Slow		
	Very Rapid	and Rapid	and Moderate	Slow	Very Slow
Slope (%)	(> 20)	(2.0 to 20)	(0.2 to 2.0)	(0.06 to 0.2)	(< 0.06)
Concave [‡]	0.10	0.10	0.10	0.10	0.10
< 1	1.20	1.40	1.60	1.80	2.00
1-5	4.20	4.90	5.60	6.30	7.00
6 - 10	4.80	5.60	6.40	7.20	8.00
11 – 20	5.40	6.30	7.20	8.10	9.00
> 20	6.00	7.00	8.00	9.00	10.00

[†]Permeability class of the least permeable layer within the upper 39 inches of the soil profile. Permeability classes can be obtained from Web Soil Survey.

‡Area from which no or very little water escapes by overland flow.

Particulate Phosphorus Component

Equation 8 presents the calculation for the particulate P component (PARTICULATE) of the UM-PMT. It is calculated as the product of the University of Maryland soil P Fertility Index Value (FIV), the combined distancebuffer factor (DBF, Eq. 2), and the Sediment Transport Factor (SED) value.

Equation 8. Particulate phosphorus transport component calculation.

PARTICULATE = DBF * SED * FIV

The Sediment Transport Factor (SED) value is determined by risk categories assigned to RUSLE or RUSLE2 scores and presented in Table 8. NRCS has moved to the use of RUSLE2 as their supported tool for predicting potential sediment loss from fields. However, in the interim as users learn RUSLE2, either RUSLE calculated within NuMan Pro software or the annual soil loss calculated by RUSLE2 for a field may be used in calculating UM-PMT.

categories.	
RUSLE or RUSLE2 ^{\dagger} "A" Value	SED Value
<1	2
1 – 2	4
2 – 3	6
3 – 4	8
>4	10
⁺ Either RUSLE or RUSLE2 annual s	oil loss value in
tons acre – may be used.	

Table 8. Distribution of RUSLE scores into risk based

Interpretation of the Final Score

After calculating each individual part of the UM-PMT as described above, the three components should be summed and that sum multiplied by a scaling factor of 0.1 as described in Eq. 1. Table 9 should be used to determine the farm management implications of the final P loss rating. Users are encouraged to run the UM-PMT multiple times with different management strategies to arrive at an implementable management strategy providing the lowest possible P loss risk. It is important to understand that the P loss rating does not have a numeric, quantitative interpretation. The P loss rating conveys only a relative meaning. Those fields in the "Low" category are predicted to have a relatively lower potential for P losses than the fields in the "Medium" category and the fields in the "Medium" category are predicted to have a relatively lower potential for P losses than the fields in the "High" category.

Table 9. In	terpretation of final UM-PMT score.
P Loss	
Rating	Generalized Interpretation of P Loss Rating
	LOW potential for P movement from this site given current management practices and site characteristics.
0-50	Soil P levels and P loss potential may increase in the future due to continued nitrogen-based nutrient management.
	Total phosphorus applications should be limited to no more than a three-year crop P removal rate applied over a three year period.
51-100	MEDIUM potential for P movement from this site given current management practices and site characteristics. Practices should be implemented to reduce P losses by surface runoff, subsurface flow, and erosion.
	Phosphorus applications should be limited to the amount of P expected to be removed from the field by the crop harvest immediately following P application or soil-test based P application recommendations.
> 100	HIGH potential for P movement from this site given current management practices and site characteristics.
	No phosphorus should be applied to this site.
	Active remediation techniques should be implemented in an effort to reduce the P loss potential from this site.

II-C2-10

University of Maryland Phosphorus Management Tool Worksheet

1.3	Combined Distance-Buffer Factor (DBF)	Multiply value from 1.1 by value from 1.2 and enter the product to the right.	
1.2	Buffer Factor (BF)	Select the appropriate buffer factor from Table 2 describing the type of buffer on the down gradient edge of the field (nearest the surface water used for 1.1).	
1.1	Distance Factor (DF)	Select the appropriate distance factor from Table 1 based on the distance from the edge of field to the nearest receiving body of water.	

Part 1. Combined	l distance-buffer	factor used for	surface runoff and	particulate bound P	components.
			Surface runon and		components.

Part 2. Particulate phosphorus component.

2.1	Combined distance-buffer factor (DBF)	Enter the value for DBF from box 1.3 to the right	
2.2	Phosphorus fertility index value (FIV)	Enter the soil test phosphorus value from the soil test report in University of Maryland Fertility Index Value (FIV) units	
2.3	Sediment transport factor (SED)	Use RUSLE in NuMan Pro or RUSLE2 to calculate the annual soil loss for the field in tons/acre. Using Table 8 enter the corresponding sediment transport risk value.	
2.4	Particulate phosphorus risk component (PARTICULATE)	Multiply DBF (2.1) times FIV (2.2) times SED (2.3) and enter the product to the right	

Part 3. Surface dissolved phosphorus source factor. Complete for each planned application and then sum. Add additional applications as needed. All P applications for the upcoming crop year should be included in the total.

3.1.a	PSC - First application	Enter the PSC from the Table 5 or calculate the PSC as described in Eq. 5	
3.1.b	Total P application - First application	Enter the total P application rate in lbs- P_2O_5 /acre.	
3.1.c	Runoff application method (AM _r)	Enter the value from Table 4 that corresponds to the application method for this P application.	
3.1	First P application factor	Multiply 3.1.a times 3.1.b times 3.1.c and enter the result	
3.2.a	PSC - Second application	Enter the PSC from the Table 5 or calculate the PSC as described in Eq. 5	
3.2.b	Total P application - Second application	Enter the total P application rate in lbs- P_2O_5 /acre.	
3.2.c	Runoff application method (AM _r)	Enter the value from Table 4 that corresponds to the application method for this P application.	
3.2	Second P application factor	Multiply 3.2.a times 3.2.b times 3.2.c and enter the result	
3.3	Total P application factor (WSP _{app-r})	Sum 3.1 and 3.2 and any other application factors that were completed on separate sheets and enter the value in the space to the right	
3.4	Degree of P saturation (DPS _{M3})	Enter the DPS _{M3} value from your soil test report.	
3.5	Surface dissolved P source risk factor (DPR _r)	Multiply the DPS _{M3} value from box 3.4 by 2 and add the product to the WSP _{app-r} value in box 3.3	

4.1	Combined distance-buffer factor (DBF)	Enter the value for DBF from box 1.3 to the right	
4.2	Surface dissolved P source risk factor (DPRr)	Enter the value from box 3.5 to the right	
4.3.a	Soil permeability class	Using Web Soil Survey, enter the soil permeability class of the dominant soil type in the field	
4.3.b	Slope	Enter the percent slope of the dominate runoff generating area of the field in the box to the right. The slope should have been measured during the site visit.	
4.3	Surface runoff transport risk factor (SR)	Using the matrix in Table 7, enter the value that corresponds to the soil permeability class (4.3.a) and slope (4.3.b) for the dominate runoff generating area of the field	
4.4	Runoff dissolved phosphorus risk component (RUNOFF)	Multiply the DBF (4.1) times the DPR _r (4.2) times the SR (4.3) and enter the product to the right	

Part 4. Surface runoff dissolved phosphorus transport component.

Part 5. Subsurface dissolved phosphorus source factor. Complete for each planned application and then sum. Add additional applications as needed. All P applications for the upcoming crop year should be included in the total.

5.1.a	PSC - First application	Enter the PSC from the Table 5 or calculate the PSC as described in Eq. 5	
5.1.b	Total P application - First application	Enter the total P application rate in lbs- P_2O_5 /acre.	
5.1.c	Subsurface transport application method - First application (AM _{sub})	Enter the value from Table 3 that corresponds to the application method for this P application.	
5.1	First P application factor	Multiply 5.1.a times 5.1.b times 5.1.c and enter the result	
5.2.a	PSC - Second application	Enter the PSC from the Table 5 or calculate the PSC as described in Eq. 5	
5.2.b	Total P application - Second application	Enter the total P application rate in lbs- P_2O_5 /acre.	
5.2.c	Subsurface transport application method - Second application (AM _{sub})	Enter the value from Table 3 that corresponds to the application method for this P application.	
5.2	Second P application factor	Multiply 5.2.a times 5.2.b times 5.2.c and enter the result	
5.3	Total P application factor (WSP _{app-sub})	Sum 5.1 and 5.2 and any other application factors that were completed on separate sheets and enter the value in the space to the right	
5.4	Degree of P saturation (DPS _{M3})	Enter the DPS _{M3} value from your soil test report.	
5.5	Subsurface dissolved P source risk factor (DPR _{sub})	Multiply the DPS _{M3} value from box 5.4 by 2 and add the product to the WSP _{app-sub} value in box 5.3	

6.3	Subsurface dissolved P transport risk component (SUBSURFACE)	Multiply the value in box 6.1 (SD) times the value in box 6.2 (DPR _{sub}) and enter the product to the right	
6.2	Subsurface dissolved P source risk factor (DPR _{sub})	Enter the value from box 5.5 to the right.	
6.1	Subsurface drainage transport factor (SD)	Use the Soil Drainage Class (4.1.a) and Hydrologic Soil Group (4.1.b) risk factors entered above to find the appropriate Subsurface Drainage Transport Factor from Table 6.	
6.1.b	Hydrologic Soil Group	Select the hydrologic soil group from the dominant map unit from Web Soil Survey and enter the appropriate risk Factor from Table 6.	
6.1.a	Soil Drainage Class	Select the soil drainage class from the dominant map unit from Web Soil Survey and enter the appropriate risk factor from Table 6.	

Part 6: Subsurface dissolved phosphorus transport component.

	, , , , ,	,	
7.1	PARTICULATE	Enter the value from box 2.4	
7.2	RUNOFF	Enter the value from box 4.4	
7.3	SUBSURFACE	Enter the value from box 6.3	
7.4	Final UM-PMT Score	Sum the values in boxes 7.1 - 7.3 and multiply the sum by 0.1. This is the final UM-PMT score. Use Table 9 to determine the final interpretative rating from this score.	

Part 7. Final University of Maryland Phosphorus Management Tool (UMPMT) calculation.

References

- Elliott H.A., Brandt R.C., Kleinman P.J., Sharpley A.N., Beegle D.B. (2006) Estimating source coefficients for phosphorus site indices. Journal of environmental quality 35:2195-201. DOI: 10.2134/jeq2006.0014.
- Kleinman P., Sullivan D., Wolf A., Brandt R., Dou Z., Elliott H., Kovar J., Leytem A., Maguire R., Moore P., Saporito L., Sharpley A., Shober A., Sims T., Toth J., Toor G., Zhang H., Zhang T. (2007) Selection of a water-extractable phosphorus test for manures and biosolids as an indicator of runoff loss potential. Journal of environmental quality 36:1357-67. DOI: 10.2134/jeq2006.0450.
- Sims J.T., Maguire R.O., Leytem A.B., Gartley K.L., Pautler M.C. (2002) Evaluation of Mehlich 3 as an Agri-Environmental Soil Phosphorus Test for the Mid-Atlantic United States of America. Soil Sci. Soc. Am. J. 66:2016-2032. DOI: 10.2136/sssaj2002.2016.

II-C2-16

Joshua M. McGrath, Frank J. Coale, Nicole M. Fiorellino

This publication, University of Maryland Phosphorus Management Tool: Technical Users Guide (EB-405) is a series of publications of the University of Maryland Extension and The Department of Environmental Science and Technology. The information presented has met UME peer review standards, including internal and external technical review. For more information on related publications and programs visit: <u>www.enst.umd.edu</u>. Please visit <u>http://extension.umd.edu/</u> to find out more about Extension programs in Maryland.

The University of Maryland Extension programs are open to any person and will not discriminate against anyone because of race, age, sex, color, sexual orientation, physical or mental disability, religion, ancestry, national origin, marital status, genetic information, political affiliation, and gender identity or expression.